





Product Specification Sheet

TropicoGreen 46

USES

- ▶ Putting Green
- ▶ Driving Ranges
- ▶ Bocce Ball
- ▶ Tennis Court
- ▶ Landscape
- ▶ Medium-Heavy Traffic

 15 Year Manufacturer's Warranty
8 Year Manufacturer's High Traffic Warranty

 ez-Flow Drainage Technology

SPECIFICATIONS

Pile Height: **5/8"**

Turf Gauge: **3/16**

Face Weight: **46 oz./yd²**

Backing Weight: **25 oz./yd²**

Total Weight: **71 oz./yd²**

Stitch Rate: **32/10cm**

Stitches/M²: **67200**

Material/Dtex: **PP5800**

Color: **Light Bi-Color Green**

Type Of Fiber: **PP Curled as thatch**

Infill Amount: **1.0 lb./psf.**

Primary Backing: **Premium GST Backing**

Tuft Bind: **8+ lb/force (ASTM D1335)**

Permeability: **26.1 inches/hr. (ASTM F1551)**

Melting Point: **150 °C (ASTM D2859)**

Grab Tear MD: **>300 lb./force (ASTM D5034)**

Grab Tear CMD: **>200 lb./force (ASTM D5034)**

Roll Width: **15 ft**

Roll Length: **100 ft**

Sq. Ft. Per Roll: **1500**

Total Roll Weight: **710 lbs**

